

# Excellent Coatings International Accessories List

<b>Product</b>	<b>Description</b>	<b>Packaging</b>	<b>Pedestrian System</b>	<b>Fire System</b>	<b>Knock –Down Finish</b>	<b>K/D II Decorative Finishes</b>	<b>Green-Line</b>	<b>Industrial Coatings</b>
Expanded Metal Lath	2.5 # galvanized, diamond metal lath Used for underlayment of the Fire System over plywood	Per bundle: 180 square ft. on 10 sheets Per pallet: 50 bundles/pallet		●				
Staple Gun	Senco Staple Gun Used to staple metal lath for Fire System over plywood	Sold individually		●				
Staples	Senco staples, galvanized, 1-inch crown, 5/8-inch leg Used to anchor metal lath to plywood	Per box: 10,000 staples/ box		●				
Deck Seal Tape/ Butyl Tape	Unique polyester fabric-backed butyl tape used for additional protection of metal flashing overlaps, deck-to-flashing interfaces, and transitions May also be used around copper drains	Per roll: 4" wide x 50 lineal ft./roll	●	●				
Fiberglass Rollers	Metal roller with grooves designed to assist laminating fiberglass to the substrate when applying the membrane	Per roller: ¾- inch x 6-inch 1- inch x 9- inch	●	●				
Fiberglass Mat	Non-woven 0.75 ounce random chop fiberglass mat	Approx. Per roll: 1,800 square ft./roll Per pallet: 16 rolls/pallet	●	●				
Patching Spreader	3 ½" x 6" polyethylene flexible spreader Used to apply Excel-Coat Patching Compound	Per box: 100 spreaders/box	●	●				
Mason Texture Gun	Nickel plated heavy gauge steel and precision machined brass may be used to spray texture; Alternative to using a "hopper gun"	Special Order Item	●	●	●			
Hopper Gun	Exterior stucco finish texture gun may be used as to apply texture coat of Excel-Coat Systems; Recommended that plastic holding bin be turned around to facilitate ease of handling	Sold separately at most hardware and building supply stores	●	●	●			
Stair Nosing Kits	Aluminum nosing designed to protect the outside edge/corner of the stair steps; Recommended to incorporate whenever applying the Excel-Coat Systems over stairs	Per kit: 14 pieces (42-inches each) or Individually in 12 foot lengths; Drill hole charge is extra per lineal ft.	●	●				
Drain(s)	6" x 6" copper drains with 2" threaded copper fitting and stainless steel drain cover attaches to standard ABS plumbing fixture	Per kit: Includes 8 copper nails, stainless steel cover & threaded copper plate Drain covers are also sold individually or in boxes of 20	●	●	●	●		

Accessory item(s) may apply under systems for which there is an indication.

(Continued on next page)

# Excellent Coatings International Accessories List (continued)

<b>Product</b>	<b>Description</b>	<b>Packaging</b>	<b>Pedestrian System</b>	<b>Fire System</b>	<b>Knock –Down Finish</b>	<b>K/D II Decorative Finishes</b>	<b>Green-Line</b>	<b>Industrial Coatings</b>
Green-Line Reinforcing Fabric	Woven fabric used to provide reinforcing to the copolymer membrane Used in conjunction with the Green-Line between slab and below-grade waterproofing systems	Per roll: 1,080 square ft. on 40" x 324" rolls					●	
Grout Tape	Reinforced tape used to apply custom designs and patterns for the K/D II Tape & Trowel and the Tape, Trowel & Skin Systems	Per roll: ¼ ", ½ " and ¾ " widths x 180 lineal ft.				●		
Excel-Coat Fibers	Loose fiber additive for Excel-Crete powders for stamp & skin applications. 1 packet used per 50 lb. bag of Excel-Crete powder	Per packet: 45 grams/packet				●		
Antiquing Powders	Dry pigmented powders added to Excel-Coat Release Agent to highlight and tint Excel-Crete K/D and K/D II applications 10 Colors available: Gray, Charcoal, Gray Slate, French Gray, Rustic Brown, Autumn Brown, Brick Red, Terra Cotta, and Walnut	By weight Dry measure packages or 50 lb. bags			●	●		
Patterned Templates	Variety of pattern templates are available; Request catalog directly from Excellent Coatings, Inc. or Authorized Distributor	Special Order Item				●		
Stamps & Skins	Variety of stamps and skins are available; Request catalog directly from Excellent Coatings, Inc. or Authorized Distributor	Special Order Item				●		
Vinyl Chips 1/4 -inch	¼-inch vinyl paint chips used in conjunction with the Epoxy Garage Floor Coating System. Request color selections directly from Excellent Coatings, Inc. or Authorized Distributor	By weight 1 & 5-gallon pails Custom blends add additional charges						●
Bleached Aluminum Oxide	Rounded bleached aluminum oxide used as a fine aggregate to broadcast onto epoxy coatings to provide a skid resistant texture.	Per lb. 36 mesh and 60 mesh						●
Calcium Chloride Test Kits	Complete concrete calcium chloride test kit used to identify moisture vapor emission for on-grade interior slabs	Kit: Sold individually	●		●	●		●

Accessory item(s) may apply under systems for which there is an indication.