

Excel-Coat Green-Line



Multi-Purpose Waterproofing Membrane

Between Slab Waterproofing/Below Grade Subterranean Wall Waterproofing/
Under Tile Applications and Pond Linings

COMPOSITION:

Excel-Coat Green-Line is a solvent-free, fluid applied waterproofing system. It is applied to substrates to provide a fully-adhered, seamless, elastomeric, waterproofing membrane. Reinforcing fabric may be installed to add strength to the membrane.

BASIC USE:

Green-Line is a monolithic membrane designed to waterproof both vertical and horizontal substrates such as between-slab, below-grade and planter applications. This product is an excellent under-tile membrane, as well as a pond or water feature membrane. The system shall be installed on a relatively smooth, structurally sound substrate. The materials employed in this system adhere to each other in such a manner that no hollow spots or voids occur. The installed waterproofing membrane will remain adhered to the substrate and maintain its elastomeric and waterproofing integrity.

LIMITATIONS:

- Do not allow product to freeze.
- Do not apply over non-structural concrete without prior written approval.

GRADE:

Excel-Coat Green-Line Waterproofing Membrane
Excel-Coat Green-Line Reinforcing Fabric

PACKAGING:

Excel-Coat Green-Line Waterproofing Membrane is available in 1 and 5 gallon containers. GL Reinforcing Fabric is available in rolls of 1080 square feet per 25 lb. roll, 40" x 324".

SHELF LIFE:

Twelve months from shipping date; stored below 80°F. Do not allow product to freeze.

COLORS:

Excel-Coat Green-Line is available in two colors, Green and Gray. Custom color matching is available upon request at an additional charge. Minimum quantities may apply; overages will apply.

JOB CONDITIONS:

Before any waterproofing work is started, the waterproofing applicator shall thoroughly examine all surfaces for any deficiencies. Should any deficiencies exist, the Architect, Owner or General Contractor shall be notified in writing and any corrections necessary shall be made.

Cold or inclement weather will effect the cure time of all Excel-Coat products. Do not install over wet substrate, in the rain or if the threat of rain exists within 24 hours.

The surface temperature should be a minimum of 45°F. All protruding pipes, conduits, holes and seams must be scaled prior to application of Excel-Coat Green-Line. The substrate shall be clean, dry, evenly planed and free of fins, sharp edges, cracks, holes, voids, curing agent residue, dust or dirt.

Proper drainage should be installed into the assembly to ensure water is expeditiously removed from the surface.

Conduits, pipes, flashing, mechanical equipment and additional items or materials provided by others shall be properly installed and secured prior to the waterproofing application.

INSTALLATION:

Refer to *Excel-Coat Green-Line Application Guide* for detailed instruction of the application procedure.

STORAGE AND HANDLING:

Store Excel-Coat Green-Line in a cool, dry area and protect from freezing. It may be necessary to stir Excel-Coat Green-Line before using. Partial containers can be resealed. Should a top skin develop on the remaining contents of a container, the physical properties and effectiveness of the contents will not be impaired. Clean mixing and application tools with water. Dispose of empty containers properly according to current Local, State and Federal regulations.

HEALTH AND HAZARD INFORMATION:

Use the product with adequate ventilation and personal protection. Users must read container label and Safety Data Sheet (SDS) for specific health and safety precautions prior to use.

AVAILABILITY:

Immediately available from Excellent Coatings International and authorized distributors.

COST:

Cost data is available from your local Excellent Coatings International authorized representative. For the name and number of the nearest local representative, call Excellent Coatings International at (800) 473-3817.

Excellent Coatings International

10880 Poplar Avenue □ Fontana □ CA 92337

Phone: (909) 823-8800 □ (800) 473-3817 □ Fax: (909) 823-6309

<http://www.excellentcoatings.com> Email: info@excellentcoatings.com

PRODUCT GUARANTEE / WARRANTY:

Excellent Coatings International warrants Excel-Coat products to be free of defects and manufactured to meet published physical properties for a period of one year following the date of shipment, provided that the product has been applied according to the manufacturer's instructions. Under this warranty, Excellent Coatings International will provide, at no charge, product in containers to replace any product proven to be defective in applications recommended by us as suitable for this product. All claims concerning the products' defects must be made within twelve months of shipment and within thirty days of discovery. Absence of such claims in writing during this period will constitute a waiver of all claims with respect to such product. This warranty is IN LIEU OF any and all other warranties, expressed or implied, including, but not limited to, any implied warranty of MERCHANTABILITY of fitness for a specific purpose.

TECHNICAL SERVICE:

Authorized local representatives are available to provide design assistance and on-site instruction for our products. Excellent Coatings International provides assistance in design and development of special applications and partial inspection. Part-time or full-time inspection and instruction are available on a fee basis upon arrangement. Technical Data available upon request.