

# Excel-Coat Sure Grip

Data Sheet

---

## Excel-Coat Skid Resistant Additive

---

### **COMPOSITION:**

Excel-Coat Sure Grip is a polycarbonate aggregate used to help increase skid resistance when mixed in Excel-Coat sealers. Because it is a polycarbonate aggregate which is clear and lightweight, it does not cause hazing of the clear sealers and stays well-suspended better in the material.

### **BASIC USE:**

To be used with Excel-Coat color and clear seal coats over Excel-Coat waterproofing and decorative systems.

### **LIMITATIONS:**

- Do not use more than the recommended quantities.

### **GRADE:**

The Excel-Coat Sure Grip is a skid resistant aggregate that can help increase skid resistance in Excel-Coat seal coats without causing hazing.

### **PACKAGING:**

The Excel-Coat Sure Grip comes in 1 quart containers (32 ounces) for use in 5 gallon pails and 6.4 ounce containers for 1 gallon pails.

### **SHELF LIFE:**

Twelve months from shipping date stored below 80°.

### **COLORS:**

Excel-Coat Sure Grip aggregate appears white in its container but is clear when suspended in Excel Coat sealers.

### **JOB CONDITIONS:**

Before any work is started, the applicator shall thoroughly examine all surfaces for any deficiencies. Should any deficiencies exist, the Architect, Owner or General Contractor shall be notified in writing and any corrections necessary shall be made.

Cold or inclement weather will affect the cure time of all Excel-Coat products. Do not install over wet substrate, in the rain or if the threat of rain exists within 24 hours.

### **INSTALLATION:**

#### **Preparation:**

Pour Excel-Coat Sure Grip into the clear or tinted sealer to be used. One quart for a 5 gallon pails and 6.4 oz. for 1 gallon pails. Mix aggregate well in the liquid with a drill motor for 2 to 3 minutes. Make sure the aggregate is well suspended. Immediately start the top coating process. If you leave the material setting for a period of time, drill motor the sealer again to assure the aggregate is suspended.

### **APPLICATION:**

Apply all Excel-Coat clear and tinted sealers in two thin coats at 250 square feet per gallon with a net yield of 125 square feet per gallon in two thin coats.

The Excel-Coat Skid resistant aggregate can be added to the last coat of sealer.

### **STORAGE AND HANDLING:**

Store Excel-Coat products in a cool dry area and protect from freezing. It will be necessary to stir Excel-Coat materials before using. Clean mixing and application tools with the appropriate solvent-based cleaners. Dispose of empty containers properly according to current Local, State and Federal regulations.

### **HEALTH AND HAZARD INFORMATION:**

Use the product with adequate ventilation; appropriate breathing apparatus (ventilators) and personal protection. Users must read container label and Safety Data Sheet (SDS) for specific health and safety precautions prior to use.

### **AVAILABILITY AND COST:**

Immediately available from Excellent Coating International and their authorized distributors. Cost data is available from your local Excellent Coatings International authorized representative. For the name and number of the nearest local representative, call Excellent Coatings International at (800) 473-3817.

### **GUARANTEE / WARRANTY:**

Excellent Coatings International warrants Excel-Coat materials to be free of defects and manufactured to meet published physical properties for a period of one year following the date of shipment, provided that the product has been applied according to the manufacturer's instructions. Under this warranty, Excellent Coatings International will provide, at no charge, product in containers to replace any product proved to be defective in applications recommended by us as suitable for this product. All claims concerning the products' defects must be made within twelve months of shipment and within thirty days of discovery. Absence of such claims in writing during this period will constitute a waiver of all claims with respect to such product. This warranty is IN LIEU OF any and all other warranties, expressed or implied, including, but not limited to, any implied warranty of MERCHANTABILITY of fitness for a specific purpose.

### **TECHNICAL SERVICE:**

Authorized local representatives are available to provide design assistance and on-site instruction for our products. Excellent Coatings International provides assistance in design and development of special applications and partial inspection. Part-time or full-time inspection and instruction are available on a fee basis upon arrangement. Technical data is available upon request.  
6/08

---

## Excellent Coatings International

10880 Poplar Avenue, Fontana, CA 92337

909-823-8800 800-473-3817 Fax: 909-823-6309

<http://excellentcoatings.com> Email: [info@excellentcoatings.com](mailto:info@excellentcoatings.com)