

EXCEL-COAT PRODUCT DATA OVERVIEW

See separate **Data Sheets** for additional technical information. See system **Application Guides** for information on the installation processes.

Product	Packaging	Use
Excel-Coat Primer 120	1, 2 & 10 gallon kits	2-component, standard, water-based primer for use on concrete or other approved surfaces
Excel-Coat Primer 120-CA	1 & 4 gallon kits	2-component, 100 VOC, water-based primer for use on concrete or other approved surfaces
Excel-Coat PC-155	1 ½ & 3 gallon kits	2-component, low VOC, solvent-based primer for concrete substrates
Excel-Coat Patching Compound	Quart & 1 gallon containers	Acrylic patch material used to smooth transitions from flashing to wood, fiberglass seams and patching minor imperfections
Excel-Coat #1	1 & 5 gallon containers	Acrylic water based resinous material used in conjunction with fiberglass mat to form the Excel-Coat waterproof membrane
Excel-Coat #200	1 & 5 gallon containers	Single component texture coat; spray or roll applied (Limited Colors)
Excel-Coat #300	1 & 5 gallon containers	High strength, durable single component acrylic colored top coat
Excel-Coat Glaze Clear Sealer	1 & 5 gallon containers	Single component, water based clear acrylic seal coat used on K/D and K/D II finishes (100 VOC)
Excel-Coat Acrylic Lacquer Sealer	1 & 5 gallon containers	Single component, solvent based, clear lacquer sealer used over decorative exterior finishes
Excel-Crete (Gray)	50 lb. bags Pallet = 50 bags	Proprietary gray Crete powder used in conjunction with Excel-Crete Clear Additive to form a polymer modified cement used for building slope and the Excel-Coat Fire System underlayment
Excel-Crete K/D (White)	50 lb. bags Pallet = 50 bags	Proprietary white Crete powder used in conjunction with Excel-Crete Tinted Additive to form a polymer modified cement used for texture and decorative finishes
Excel-Crete Clear Additive	1 & 5 gallon containers	Polymer additive for use with Excel-Crete gray powder, or K/D White Powder to form polymer modified cement
Excel-Crete Tinted Additive	1 & 5 gallon containers	Polymer tinted additive for use with white Excel-Crete K/D powder to provide a decorative spray, trowelled or stamped finish
Excel-Crete Retarder	27 gram packet	Dry food-grade citric acid powder to be used in conjunction with the Excel-Crete and Additive products to slow the setting/curing time. Adds to time for workability of Excel-Crete products (Gray and White).
Excel-Coat Stay-Clean Stamp Release & Cleaning Agent (formerly Release Agent)	1 & 5 gallon containers	Solvent-based clear liquid for use with skins and stamps to reduce sticking and facilitate ease of removal during application
Excel-Coat MERT	1 & 5 gallon containers	Clear Acrylic coating that is a CLEAR SEAL COAT on the Excel-Coat BC-100 Colored Quarts System. Clear MERT is also used to seal tape when skins and Release Agent are to be used
Excel-Thane "MCU-400"	1 gallon & 5 gallon containers	Clear High Gloss urethane seal coat used over decorative exterior concrete surfaces (400 VOC)

Continued on next page

Product	Packaging	Use
Excel-Thane MCU “400”, MCU “250”, MCU “100”	1 gallon & 5 gallon containers	Clear High Gloss urethane seal coatings for use over decorative aggregate exterior concrete surfaces (100 VOC, 250 VOC & 400 VOC)
Excel-Crete Reinforcing Fibers	45 gram packet	Pre-measured packet of loose chopped fiberglass for use with Excel-Crete Polymer Modified Cement toppings to enhance strength and reduce surface cracking
Excel-Coat Sure Grip	1 Quart containers	Polycarbonate aggregate that may be mixed with Excel-Coat Color and Clear Top Coats to add a light degree of anti-skid properties. Used One Quart per 5 gallon container of sealer/topcoat.
Excel-Poxy 107	3 gallon kits	100% solids clear epoxy trowel-down aggregate binder used in the ¼ inch Flooring System and as a primer coating for concrete.
Excel-Poxy 127	3 gallon kits	Two-component, 100% solids, clear epoxy top and seal coating for flooring applications. Used for industrial floors and with the Garage Floor Vinyl Chip system
Excel-Poxy 128	3 gallon kits	Two-component, 100% solids, pigmented epoxy top and seal coating for flooring applications. Used for industrial floors and with the Garage Floor Vinyl Chip system
Excel-A-Spartic 87 Clear	2 gallon & 10 gallon kits	Two-component, fast drying, aliphatic polyaspartic ester coating. Ideal product when a low odor, fast turnaround and a non-yellowing system are essential.